

TELEDYNE ANALYTICAL INSTRUMENTS

 ϵ

16830 Chestnut Street, City of Industry, California 91748-1020, USA TEL: 626.934.1500 • FAX: 626.934.1651 • www.teledyne-ai.com

Model Number

Description

3220

Percent oxygen monitoring system

CONTROL MODULE:

- 19" relay rack mounting cage for up to eight channel modules
- System power on/off switch, system alarm and bypass switch with indicator lights
- Common alarm relays, Form "C" contacts (SPDT)
- Universal power supply, 100-240 VAC 50/60 Hz

CHANNEL MODULE:

- Universal power supply, 100-240VAC, 50/60Hz
- 0-10 VDC analog output
- Two fully adjustable alarm set points and indicator lights
- · Automatic diagnostics; failure alarm relay and indicator light
- 1MAN calibration

CHANNEL MODULE OPTIONS:

- M 4-20 mADC output (replaces 0-10 VDC output)

Price-adder options

System cabinet / freestanding enclosure with blower (P/N: D-68170)

System cooling module (P/N: B-00447)

Wall mount and purged enclosures

Flow-through adapter - for use with calibration gas (P/N: A-12698)

Channel module blank covers (P/N: A-68423)

2 year extended warranty (does not include consumables such as sensors)

3 year extended warranty (does not include consumables such as sensors)

Additional instruction manual



