



# HALO 3 H<sub>2</sub>O

## Trace Level Moisture Analyzer

GASES & CHEMICALS

CEMS

ENERGY

SEMI & HB LED

ATMOSPHERIC

LAB & LIFE SCIENCE

### Designed for trace level moisture analysis, the HALO 3 H<sub>2</sub>O offers:

- Sub parts per billion (ppb) moisture detection capability in an array of gases
- Absolute measurement (freedom from calibration gases)
- Wide dynamic range—over four orders of magnitude
- Low cost of ownership and operational simplicity
- Clean technology—no external calibration gases required
- Low gas consumption to conserve rare and costly gas
- Versatility—trace-level detection in various gas matrices

The HALO 3 H<sub>2</sub>O analyzer provides users with the unmatched accuracy, reliability, speed of response and ease of operation that users of Tiger Optics analyzers know and expect. Featuring Tiger Optics' powerful Cavity Ring-Down Spectroscopy-based moisture sensor in a very compact and economic analyzer design, this versatile analyzer allows users to measure moisture in most inert, corrosive and toxic gases with just one device. Users also enjoy freedom from requirements such as periodic

sensor maintenance, span calibrations, purifier replacement and pump rebuilds. As a result, the HALO 3 H<sub>2</sub>O analyzer is ideally suited to many applications where moisture measurement is extremely critical. These applications include fixed bulk gas continuous quality control, portable mobile analytical carts, process tool monitoring, air separation, gas cylinder quality control and many other demanding applications.

# HALO 3 H<sub>2</sub>O

## Trace Level Moisture Analyzer



Performance		Dimensions	
Operating range	See table on next page	<b>H x W x D [in (mm)]</b>	
Detection limit (LDL, 3σ/24h)	See table on next page	Standard sensor	8.73 x 8.57 x 23.6 (222 x 218 x 599)
Precision (1σ, greater of)	± 0.75% or 1/3 of LDL	Sensor rack	8.73 x 19.0 x 23.6 (222 x 483 x 599)
Accuracy (greater of)	± 4% or LDL	(fits up to two sensors)	
Speed of response	< 1 minute to 90%	Weight	
Environmental conditions	10°C to 40°C 30% to 80% RH (non-condensing)	Standard sensor	28 lbs (12.7 kg)
Storage temperature	-10°C to 50°C	Electrical and Interfaces	
Gas Handling System and Conditions		Platform	Max series analyzer
Wetted materials	316L stainless steel (corrosive gas version optional) 10 Ra surface finish	Alarm indicators	2 user programmable 1 system fault Form C relays
Gas connections	1/4" male VCR inlet and outlet	Power requirements	90 – 240 VAC, 50/60 Hz
Leak tested to	1 x 10 <sup>-9</sup> mbar l / sec	Power consumption	40 Watts max.
Inlet pressure	10 – 125 psig (1.7 – 9.6 bara)	Signal output	Isolated 4–20 mA per sensor
Flow rate	0.05 – 1.8 slpm	User interfaces	5.7" LCD touchscreen 10/100 Base-T Ethernet USB, RS-232, RS-485 Modbus TCP (optional)
Sample gases	Most inert, toxic, passive and corrosive matrices	Data storage	Internal or external flash drive
Gas temperature	Up to 60°C	Certification	CE Mark

# HALO 3 H<sub>2</sub>O

## Trace Level Moisture Analyzer

Performance, H <sub>2</sub> O:		Range	LDL (3σ)	Precision (1σ) @ zero
INERT/ PASSIVE GASES	In Nitrogen	0 – 20 ppm	1.2 ppb	0.4 ppb
	In Helium	0 – 4 ppm	0.25 ppb	0.1 ppb
	In Argon	0 – 9 ppm	0.6 ppb	0.2 ppb
	In Hydrogen	0 – 16 ppm	1.0 ppb	0.4 ppb
	In Deuterium ( <sup>2</sup> H <sub>2</sub> )	0 – 14 ppm	0.9 ppb	0.3 ppb
OXYGENATED GASES	In Oxygen	0 – 12 ppm	0.7 ppb	0.25 ppb
	In Clean Dry Air (CDA)	0 – 18 ppm	1.2 ppb	0.4 ppb
	In CO	0 – 24 ppm	1.5 ppb	0.5 ppb
	In CO <sub>2</sub> (standard / high range)	0 – 25 ppm / 0 – 70 ppm	2.0 ppb / 8 ppb	0.7 ppb / 3 ppb
	In SO <sub>2</sub>	0 – 60 ppm	4 ppb	1.2 ppb
RARE GASES	In Neon	0 – 5 ppm	0.3 ppb	0.1 ppb
	In Krypton	0 – 11 ppm	0.6 ppb	0.2 ppb
	In Xenon	0 – 13 ppm	0.8 ppb	0.3 ppb
COR- ROSIVE GASES	In Cl <sub>2</sub> *	0 – 25 ppm	1.5 ppb	0.5 ppb
	In HCl†	0 – 50 ppm	3 ppb	1.0 ppb
	In HBr‡	0 – 100 ppm	12 ppb	4 ppb
FLUORINATED GASES	In SF <sub>6</sub>	0 – 15 ppm	1.0 ppb	0.4 ppb
	In NF <sub>3</sub>	0 – 20 ppm	2.5 ppb	0.9 ppb
	In CF <sub>4</sub>	0 – 15 ppm	4 ppb	1.2 ppb
	In C <sub>2</sub> F <sub>6</sub>	0 – 15 ppm	3 ppb	1.0 ppb
	In C <sub>3</sub> F <sub>8</sub>	0 – 20 ppm	3 ppb	1.0 ppb
	In C <sub>4</sub> F <sub>6</sub>	0 – 25 ppm	150 ppb	50 ppb
	In C <sub>4</sub> F <sub>8</sub>	0 – 20 ppm	3 ppb	1.0 ppb
	In C <sub>5</sub> F <sub>8</sub>	0 – 32 ppm	30 ppb	10 ppb
	In H <sub>2</sub> Se <sup>§</sup>	0 – 70 ppm	30 ppb	10 ppb

\*Corrosive gas version recommended for H<sub>2</sub>O concentration that could exceed 10 ppm

†Corrosive gas version recommended for H<sub>2</sub>O concentration that could exceed 1 ppm

‡Corrosive gas version required

§Detection in H<sub>2</sub>Se requires special analyzer configuration, contact us for more information.

Contact us for additional analytes and matrices.

U.S. Patent # 7,277,177

**Tiger Optics, LLC**

275 Gibraltar Road, Horsham, PA 19044

Phone: +1 (215) 656 4000 · Fax: +1 (215) 343 7168

sales@tigeroptics.com · www.tigeroptics.com



**Tigeroptics**  
A Process Insights Company

6/2020A