

PRODUCT DATASHEET

Prismatic™ 3

Multi-Species Gas Analyzer



The Prismatic 3 features:

- Simultaneous parts-per-billion detection of CO, CO₂, H₂O and CH₄
- Low Cost of Ownership: no calibration or utility gas requirements
- Ideal analyzer to meet Hydrogen purity requirements of SAE J2719 and ISO 14687:2019
- Easy to install and use per ASTM Standard Test Method D7941
- Powerful Cavity Ring-Down Spectroscopy (CRDS) technology

With the Prismatic™ 3 laser-based, multi-species trace gas analyzer, Tiger Optics takes a quantum leap forward.

The Prismatic 3 provides a critical tool for use in a variety of applications in both research and industrial settings, where real-time, on-line gas monitoring is essential. The Prismatic 3 is ideally suited for fuel-cell hydrogen purity monitoring throughout the entire hydrogen supply chain – from production to transportation and storage to the fueling station.

This compact, CRDS-based analyzer offers simultaneous detection of H₂O, CO, CO₂ and CH₄ from parts-per-billion to parts-per-million levels to ensure purity requirements in line with SAE J2719 and ISO 14687:2019.

What's more, the Prismatic 3 is very easy to install and operate with integrated touchscreen and intuitive graphical user interface to allow efficient data trending and analysis. The cost of ownership is extremely low, with no calibration, spare parts or utility gases required.

Prismatic 3

Multi-Species Gas Analyzer

Performance

Operating range:	See table on next page
Detection limit (LDL, 3σ/24h):	See table on next page
Precision (1σ, greater of):	\pm 0.75% or 1/3 of LDL
Accuracy (greater of):	\pm 4% or LDL
Speed of response:	< 5 minutes to 95% (in 4-channel operation)
Environmental conditions:	10°C to 40°C 30% to 80% RH (non-condensing)
Storage temperature:	-10°C to 50°C



Gas Handling System and Conditions

Wetted materials:	316L stainless steel, 10 Ra surface finish
Gas connections:	1/4" male VCR inlet and outlet
Leak tested to:	1 x 10 ⁻⁹ mbar l / sec
Inlet pressure:	10 – 125 psig (1.7 – 9.6 bara)
Flow rate:	< 1 slpm (gas dependent)
Sample gases:	Inert gases, hydrogen and oxygen
Gas temperature:	Up to 60°C

Dimensions & Weight

Standard sensor:	H × W × D 8.73 × 19.0 × 23.6 in (222 × 483 × 599 mm) (19" rack-mountable)
Standard sensor weight:	50 lbs (22.7 kg) estimated

Electrical & Interfaces

Alarm indicators:	1 user programmable per channel, 1 system fault, Form C relays
Power requirements:	90 – 240 VAC, 50/60 Hz
Power consumption:	300 Watts max.
Signal output:	Isolated 4–20 mA per channel
User interfaces:	10.4" LCD touchscreen. 10/100 Base-T Ethernet. RS-232, RS-485
Data storage:	Internal or external flash drive

Performance in N ₂	Range	LDL (3σ)	Precision (1σ) @ zero
Methane (CH₄):	0 – 100 ppm	100 ppb	35 ppb
Moisture (H₂O):	0 – 40 ppm	100 ppb	35 ppb
Carbon Monoxide (CO):	0 – 500 ppm	50 ppb	20 ppb
Carbon Dioxide (CO₂):	0 – 1000 ppm	200 ppb	70 ppb

Performance in H ₂	Range	LDL (3σ)	Precision (1σ) @ zero
Methane (CH₄):	0 – 100 ppm	100 ppb	35 ppb
Moisture (H₂O):	0 – 25 ppm	100 ppb	35 ppb
Carbon Monoxide (CO):	0 – 500 ppm	50 ppb	20 ppb
Carbon Dioxide (CO₂):	0 – 1000 ppm	320 ppb	110 ppb

Performance in Ar	Range	LDL (3σ)	Precision (1σ) @ zero
Methane (CH₄):	0 – 90 ppm	100 ppb	35 ppb
Moisture (H₂O):	0 – 18 ppm	40 ppb	15 ppb
Carbon Monoxide (CO):	0 – 400 ppm	40 ppb	15 ppb
Carbon Dioxide (CO₂):	0 – 800 ppm	160 ppb	55 ppb

Performance in O ₂	Range	LDL (3σ)	Precision (1σ) @ zero
Methane (CH₄):	0 – 90 ppm	100 ppb	35 ppb
Moisture (H₂O):	0 – 20 ppm	50 ppb	20 ppb
Carbon Monoxide (CO):	0 – 400 ppm	45 ppb	15 ppb
Carbon Dioxide (CO₂):	0 – 850 ppm	170 ppb	60 ppb

PREMIUM INSIGHTS – GAIN REAL-TIME INSIGHT INTO YOUR PROCESS

Process Insights' products and solutions deliver innovative and differentiated analysis and measurement solutions and technologies that add high value to our customers and protect the environment.

Our commitment is to deliver smart and affordable innovation that optimizes process, improves safety, and transforms our world.

CENTERS OF EXCELLENCE

PROVIDING PROVEN SOLUTIONS FROM A GLOBAL TECHNOLOGY LEADER



Tiger Optics

275 Gibraltar Road
Horsham, PA 19044
USA
+1 215 656 4000
sales@tigeroptics.com
service@tigeroptics.com
www.tigeroptics.com

Process Insights – The Americas

4140 World Houston Parkway
Suite 180
Houston, TX 77032
USA
+1 713 947 9591
info@process-insights.com

Process Insights – EMEA

ATRICOM
Lyoner Strasse 15
60528 Frankfurt
Germany
+49 69 20436910
info@process-insights.com

Process Insights – APAC

Wujiang Economic and Technology
Development Zone
No. 258 Yi He Road, 215200 Suzhou
Jiangsu Province China
+86 400 086 0106
info@process-insights.com

OUR PREMIUM GLOBAL BRANDS

