

PRODUCT DATASHEET

HALO 3™ H₂O

TRACE LEVEL MOISTURE ANALYZER



Designed for trace level moisture analysis, the HALO 3 H₂O offers:

- Sub parts per billion (ppb) moisture detection capability in an array of gases
- Absolute measurement (freedom from calibration gases)
- Wide dynamic range—over four orders of magnitude
- Low cost of ownership and operational simplicity
- Clean technology—no external calibration gases required
- Low gas consumption to conserve rare and costly gas
- Versatility—trace-level detection in various gas matrices

The HALO 3 H₂O™ analyzer provides users with the unmatched accuracy, reliability, speed of response and ease of operation that users of our analyzers know and expect. Featuring our powerful Cavity Ring-Down Spectroscopy-based moisture sensor in a very compact and economic analyzer design, this versatile analyzer allows users to measure moisture in most inert, corrosive and toxic gases with just one device. Users also enjoy freedom from requirements such as periodic sensor maintenance, span calibrations, purifier replacement and pump rebuilds. As a result, the HALO 3 H₂O analyzer is ideally suited to many applications where moisture measurement is extremely critical. These applications include fixed bulk gas continuous quality control, portable mobile analytical carts, process tool monitoring, air separation, gas cylinder quality control and many other demanding applications.

Specifications

Performance

Operating range:	See table on next page
Detection limit (LDL, 3σ/24h):	See table on next page
Precision (1σ, greater of):	± 0.75% or 1/3 of LDL
Accuracy (greater of):	± 4% or LDL
Speed of response:	< 1 minute to 90%
Environmental conditions:	10°C to 40°C, 30% to 80% RH (non-condensing)
Storage temperature:	-10°C to 50°C

Gas Handling System and Conditions

Wetted materials:	316L stainless steel (corrosive gas version optional) 10 Ra surface finish
Gas connections:	1/4" male VCR inlet and outlet
Leak tested to:	1 x 10 ⁻⁹ mbar l / sec
Inlet pressure:	10 – 125 psig (1.7 – 9.6 bara)
Flow rate:	0.05 to 1.8 slpm
Sample gases:	Most inert, toxic, passive and corrosive matrices
Gas temperature:	Up to 60°C

Dimensions & Weight

Standard sensor:	H x W x D: 8.73 x 8.57 x 23.6 in (222 x 218 x 599 mm)
Sensor rack (fits up to two sensors):	H x W x D: 8.73 x 19.0 x 23.6 in (222 x 483 x 599 mm)
Standard sensor weight:	28 lbs (12.7 kg)

Electrical and Interfaces

Platform:	Max series analyzer
Alarm indicators:	2 user programmable, 1 system fault, Form C relays
Power requirements:	90 – 240 VAC, 50/60 Hz
Power consumption:	40 Watts max.
Signal output:	Isolated 4–20 mA per sensor
User interfaces:	5.7" LCD touchscreen, 10/100 Base-T Ethernet USB, RS-232, RS-485 Modbus TCP (optional)
Data storage:	Internal or external flash drive
Certification:	CE Mark

Performance, H ₂ O		Range	LDL (3σ)	Precision (1σ) @ zero
INERT/PASSIVE GASES	In Nitrogen:	0 – 20 ppm	1.2 ppb	0.4 ppb
	In Helium :	0 – 4 ppm	0.25 ppb	0.1 ppb
	In Argon:	0 – 9 ppm	0.6 ppb	0.2 ppb
	In Hydrogen:	0 – 16 ppm	1.0 ppb	0.4 ppb
OXYGENATED GASES	In Oxygen:	0 – 12 ppm	0.7 ppb	0.25 ppb
	In Clean Dry Air (CDA):	0 – 18 ppm	1.2 ppb	0.4 ppb
	In CO:	0 – 24 ppm	1.5 ppb	0.5 ppb
	In CO ₂ standard: high range:	0 – 25 ppm	2.0 ppb	0.7 ppb
		0 – 70 ppm	8 ppb	3 ppb
	In SO ₂ :	0 – 60 ppm	4 ppb	1.2 ppb
RARE GASES	In Neon:	0 – 5 ppm	0.3 ppb	0.1 ppb
	In Krypton:	0 – 11 ppm	0.6 ppb	0.2 ppb
	In Xenon:	0 – 13 ppm	0.8 ppb	0.3 ppb
	In Deuterium (² H ₂):	0 – 14 ppm	0.9 ppb	0.3 ppb
CORROSIVE GASES	In Cl ₂ *:	0 – 25 ppm	1.5 ppb	0.5 ppb
	In HCl†:	0 – 50 ppm	3 ppb	1.0 ppb
	In HBr*:	0 – 100 ppm	12 ppb	4 ppb
	In 10% BCl ₃ /90% N ₂ :	0 – 20 ppm	12 ppb	4 ppb
FLUORINATED GASES	In SF ₆ :	0 – 15 ppm	1.0 ppb	0.4 ppb
	In NF ₃ :	0 – 20 ppm	2.5 ppb	0.9 ppb
	In CF ₄ :	0 – 15 ppm	4 ppb	1.2 ppb
	In C ₂ F ₆ :	0 – 15 ppm	3 ppb	1.0 ppb
	In C ₃ F ₈ :	0 – 20 ppm	3 ppb	1.0 ppb
	In C ₄ F ₆ :	0 – 25 ppm	150 ppb	50 ppb
	In C ₄ F ₈ :	0 – 20 ppm	3 ppb	1.0 ppb
	In C ₅ F ₈ :	0 – 32 ppm	30 ppb	10 ppb
HYDRIDE GASES	In H ₂ S:	0 – 40 ppm	200 ppb	70 ppb
	In H ₂ Se‡:	0 – 70 ppm	30 ppb	10 ppb
	In 1% GeH ₄ /99% H ₂ :	0 – 16 ppm	7 ppb	2.5 ppb
	In 10% GeH ₄ /90% H ₂ :	0 – 16 ppm	35 ppb	12 ppb
	In 1% PH ₃ /99% H ₂	0 – 4 ppm	1 ppb	0.4 ppb
	In PH ₃ :	0 – 75 ppm	500 ppb	170 ppb
	In 1% B ₂ H ₆ /99% H ₂	0 – 16 ppm	30 ppb	10 ppb
	In 2% B ₂ H ₆ /98% H ₂	0 – 16 ppm	30 ppb	10 ppb

*Corrosive gas version required

†Corrosive gas version recommended for H₂O concentration that could exceed 1 ppm

‡Detection in H₂Se requires special analyzer configuration dedicated to service in H₂Se. Contact us for more information

Contact us for additional analytes, matrices and ranges.

U.S. Patent # 7,277,177

GAIN REAL-TIME INSIGHT INTO YOUR PROCESS

Process Insights delivers premium analytical sensors, analyzers, instrumentation, software and solutions that are mission-critical to keep your operations, personnel, and the environment safe. Our commitment to customer satisfaction is evident through our diverse range of products, programs, and services, designed to accommodate various budgets and application needs.

CENTERS OF EXCELLENCE | PROVIDING PROVEN SOLUTIONS

Process Insights – The Americas

14400 Hollister Street, Suite 800B, Houston, TX 77066, USA +1 713 947 9591
info.americas@process-insights.com

Process Insights – EMEA

ATRICOM, Lyoner Strasse 15, 60528 Frankfurt, Germany +49 69 20436910
info.emeai@process-insights.com

Process Insights – APAC

Wujiang Economic and Technology, Development Zone, No. 258 Yi He Road, 215200 Suzhou, Jiangsu Province, China +86 400 086 0106
info.apac@process-insights.com
info.cn@process-insights.com

For a complete list of sales & manufacturing sites, please visit:
<https://www.process-insights.com/about-us/locations/>

