



Model Number	Description
1223A	Flush panel-mount, flammable gas detection unit capable of accepting up to three monitoring channels One channel Two channels Three channels
1223B	Same as 1223A except wall mounted enclosure with viewing window One channel Two channels Three channels



- Microprocessor controlled
- Password protection
- LCD display
- Touch key controls
- Two fully adjustable alarm set points and indicator lights
- Programmable alarm relay functions
- Automatic diagnostics with failure alarm relay and indicator light
- 1MAN calibration
- Time delay on start up
- 0-10 VDC output
- Welded sheet steel enclosures
- Universal power supply 100-240 VAC 50/60 Hz with "power on" indicator light

CHANNEL MODULE OPTIONS:

- M 4-20 mADC output (replaces 0-10 VDC output)
- T Two sensors per channel

DETECTOR:

- Detector assembly (Class I, Div 1, Groups B, C, & D) includes combustible probe and explosion-proof J-box (P/N: A-12431)
- Spare combustible detector (P/N: B-12093)
- Spare explosion proof junction box (P/N: A-12430)

Price-adder options

- Calibration adapter - 1 per sensor (P/N: A-11091)
- Flow-through adapter - for use with calibration gas (P/N: A-12698)
- Channel module blank covers (P/N: A-30398)
- 2 year extended warranty (does not include consumables such as sensors)
- 3 year extended warranty (does not include consumables such as sensors)
- Additional instruction manual

Ask about our Preventative Maintenance Program