



Model Number	Description
--------------	-------------

TURBO2	Portable Trace Oxygen (O ₂) analyzer
--------	--

- Ranges: 0-100, 0-1000, 0-10,000 ppm O₂ 0-25% cal. range
- Sensor: Micro-fuel Cell class S-2C
- Integral analog meter readout
- Rechargeable NiCad batteries with 110 VAC, 50 / 60 Hz integral charging circuit
- Nickel-plated brass quick-disconnect fittings; mating set (3) of male fittings (vent, sample, calibration), length of calibration hose
- Instruction manual

No-charge options

100 VAC, 50 / 60 Hz recharge circuit

220 VAC, 50 / 60 Hz recharge circuit



Price-adder options

Stainless-steel quick-disconnect fittings (female); mating set (3) of stainless-steel male fittings (vent, sample, calibration)

Special ranges

Spare sensor - Class S-2C Micro-fuel Cell (P/N: C-06689-S2C)

Carrying case (P/N: C-01134)

2 year extended warranty (does not include consumables such as sensors)

3 year extended warranty (does not include consumables such as sensors)

Additional instruction manual

TURBO2P	TURBO2 with pump
---------	------------------

Price-adder options

2 year extended warranty (does not include consumables such as sensors)

3 year extended warranty (does not include consumables such as sensors)

Additional instruction manual

Ask about our Preventative Maintenance Program